

PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION  
International Bureau

## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

<b>(51) International Patent Classification <sup>7</sup> :</b> <b>C07C 29/10</b>	<b>A1</b>	<b>(11) International Publication Number:</b> <b>WO 00/35840</b> <b>(43) International Publication Date:</b> 22 June 2000 (22.06.00)
<b>(21) International Application Number:</b> PCT/EP99/10047 <b>(22) International Filing Date:</b> 13 December 1999 (13.12.99) <b>(30) Priority Data:</b> 98204232.7           14 December 1998 (14.12.98)   EP 99201349.0           29 April 1999 (29.04.99)       EP <b>(71) Applicant:</b> SHELL INTERNATIONALE RESEARCH MAATSCHAPPIJ B.V. [NL/NL]; Carel van Bylandtlaan 30, NL-2596 HR The Hague (NL). <b>(72) Inventor:</b> VAN KRUCHTEN, Eugene, Marie, Godfried, An- dre; Badhuisweg 3, NL-1031 CM Amsterdam (NL).	<b>(81) Designated States:</b> AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).  <b>Published</b> <i>With international search report.</i>	
<b>(54) Title:</b> QUATERNARY PHOSPHONIUM SALT CATALYSTS IN CATALYTIC HYDROLYSIS OF ALKYLENE OXIDES		
<b>(57) Abstract</b>  <p>A process for the preparation of alkylene glycols by reacting an alkylene oxide with water in the presence of at least one ionic composition of a quaternary phosphonium cation of the general formula <math>R_1R_2R_3R_4P^+</math> whereby each of <math>R_1</math>, <math>R_2</math>, <math>R_3</math> and <math>R_4</math>, independently, may be an alkyl, cycloalkyl, aryl, alkylaryl or arylalkyl group having from 1 to 10 carbon atoms, each of which may carry one or more substituents, or be attached to a polymer and an anion other than metalate or halogen.</p>		

**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

QUATERNARY PHOSPHONIUM SALT CATALYSTS IN CATALYTIC  
HYDROLYSIS OF ALKYLENE OXIDES

The present invention relates to a process for the preparation of alkylene glycols by reacting an alkylene oxide with water in the presence of a catalytic composition.

5     Background of the invention

Alkylene glycols, in particular monoalkylene glycols, are of established commercial interest. For example, monoalkylene glycols are being used in anti-freeze compositions, as solvents and as base materials in the  
10     production of polyalkylene terephthalates e.g. for fibres or bottles.

The production of alkylene glycols by liquid phase hydrolysis of alkylene oxide is known. The hydrolysis is performed without a catalyst by adding a large excess of  
15     water, e.g. 20 to 25 moles of water per mole of alkylene oxide, or it is performed with a smaller excess of water in a catalytic system. The reaction is considered to be a nucleophilic substitution reaction, whereby opening of the alkylene oxide ring occurs, water acting as the  
20     nucleophile. Because the primarily formed monoalkylene glycol also acts as a nucleophile, as a rule a mixture of monoalkylene glycol, dialkylene glycol and higher alkylene glycols is formed. In order to increase the selectivity to monoalkylene glycol, it is necessary to  
25     suppress the secondary reaction between the primary product and the alkylene oxide, which competes with the hydrolysis of the alkylene oxide.

One effective means for suppressing the secondary reaction is to increase the relative amount of water  
30     present in the reaction mixture. Although this measure

improves the selectivity towards the production of the monoalkylene glycol, it creates a problem in that large amounts of water have to be removed for recovering the product.

5           Considerable efforts have been made to find an alternative for increasing the reaction selectivity without having to use a large excess of water. Usually these efforts have focused on the selection of more active hydrolysis catalysts and various catalysts have  
10           been disclosed.

Both acid and alkaline hydrolysis catalysts have been investigated, whereby it would appear that the use of acid catalysts enhances the reaction rate without significantly affecting the selectivity, whereas by using  
15           alkaline catalysts generally lower selectivities with respect to the monoalkylene glycol are obtained.

Certain anions, e.g. bicarbonate (hydrogen carbonate), bisulphite (hydrogen sulphite), formate and molybdate, are known to exhibit good catalytic activity  
20           in terms of alkylene oxide conversion and selectivity towards monoalkylene glycol. However when the salts of these anions are used as the catalyst in a homogeneous system, work-up of the reaction product by distillation will pose a problem because the salts are poorly soluble  
25           in the glycol and tend to make it semi-solid. Quaternary ammonium salts remain soluble in the glycol reaction product.

High conversions, good selectivity and a low water/alkylene oxide ratio can be obtained with the  
30           process, disclosed in EP-A 0 156 449 and EP-A 0 160 330 (both of Union Carbide). According to these documents the hydrolysis of alkylene oxides is carried out in the presence of a selectivity-enhancing metalate anion-containing material, preferably a solid having  
35           electropositive complexing sites having affinity for the

metalate anions. The said solid is preferably an anion exchange resin, in particular a styrene-divinyl benzene copolymer. The electropositive complexing sites are in particular quaternary ammonium, protonated tertiary amine or quaternary phosphonium. No specific advantage is attributed to the quaternary phosphonium. The metalate anions are specified as molybdate, tungstate, metavanadate, hydrogenpyrovanadate and pyrovanadate anions. A complication of this process is that the alkylene glycol-containing product stream also comprises a substantial amount of metalate anions, displaced from the electropositive complexing sites of the solid metalate anion containing material. In order to reduce the amount of metalate anions in the alkylene glycol product stream, this stream is contacted with a solid having electropositive complexing sites associated with anions which are replaceable by the said metalate anions. In WO 95/20559 (Shell) there is disclosed a process for the preparation of alkylene glycols wherein an alkylene oxide is reacted with water in the presence of a catalyst composition comprising a solid material having one or more electropositive sites, which are coordinated with one or more anions other than metalate or halogen anions, e.g. bicarbonate, bisulphite and carboxylate, with the proviso that when the solid material is an anionic exchange resin of the quaternary ammonium type and the anion is bicarbonate the process is performed in the substantial absence of carbon dioxide. According to this document, the presence of carbon dioxide in the feed is detrimental to the catalytic effect of bicarbonate-exchanged resins of the quaternary ammonium type.


As indicated above, salts composed of catalytic anions and quaternary ammonium cations can be used in a homogeneous system as well as in a heterogeneous system. Indeed, in heterogeneous systems such quaternary ammonium

ions are the traditionally used cations of most anion exchange resins. A drawback shared by these quaternary ammonium compounds is their limited tolerance to heat. In practising the process of alkylene oxide hydrolysis according to WO 95/20559 with catalyst compositions based on conventional organic quaternary ammonium ion exchangers it has been found, that under severe alkylene oxide hydrolysis reaction conditions (high temperature and/or long service) the catalytic activity (selectivity and/or conversion) and/or swelling behaviour of the conventional resin-based catalysts tends to deteriorate.

In US-A 4,160,116 (Showa Denko) there is disclosed a process for the production of an alkylene glycol by hydrating an alkylene oxide in the presence a substantial amount of carbon dioxide using a quaternary phosphonium salt of iodine, bromide or chlorine as a catalyst.

#### Summary of the invention

The present invention relates to a process for the preparation of alkylene glycols by reacting an alkylene oxide with water in the presence of at least one ionic composition of a quaternary phosphonium cation of the general formula



Whereby each of  $R_1$ ,  $R_2$ ,  $R_3$  and  $R_4$ , independently, may be an alkyl, cycloalkyl, aryl, alkylaryl or arylalkyl group having from 1 to 10 carbon atoms, each of which may carry one or more substituents or be attached to a polymer, and an anion other than metalate or halogen.

The anion is preferably chosen from the group of bicarbonate, bisulphite and the carboxylic acid derivatives. When the anion is a carboxylic acid, it is preferably chosen from the group of formate and citrate.

Generally, carbon dioxide is not required.

In a preferred embodiment of the present invention, the quaternary phosphonium cation is immobilised on a solid support, such as an anion exchange resin.

Detailed description of the invention

5       As such, the quaternary phosphonium compounds as herein defined are effective as alkylene oxide hydrolysis catalysts in a homogeneous liquid reaction system. However, a particular advantage of these quaternary phosphonium compounds emerges when they are used in a  
10       heterogeneous reaction system, wherein the quaternary phosphonium cations constitute the electropositive sites of a solid support, as defined in WO 95/20559. In particular, when the solid support is a strongly basic anionic exchange resin the base of which is a quaternary  
15       phosphonium cation according to the present invention, a catalytic composition is formed - with the anion according to the invention - which is stable and which retains its selectivity and stability under severe reaction conditions as well as being more resistant to  
20       swelling.


Any of a large number of ion exchange resin (IER) types can be used as the solid support, in particular the strongly basic (anionic) IER's wherein the basic groups are quaternary phosphonium groups attached (i.e.  
25       adsorbed, reacted or grafted) to a polymeric backbone. Suitable polymeric backbones include high molecular weight polymers and co-polymers, e.g. addition and condensation polymers, including polyalkylene, polyester, polycarbonate, polyurethane, formaldehyde resins, etc.  
30       Commercially available IER's include resins based on polyacrylate or styrene-divinylbenzene copolymers. Many of these IER's are purely organic polymers, but also silica based resins, such as polysiloxanes, can conveniently be used. Alternative materials having the  
35       quaternary phosphonium type of electropositive complexing

site bonded by adsorption, reaction or grafting, include those of inorganic nature, such as carbon, silica, silica-alumina, zeolites, glass and clays such as hydrotalcite.

5       The catalyst composition according to the invention can be completed by immobilisation of the catalytically active anion on the solid support by adding it in aqueous solution to a suspension of the solid support, which may or may not be adapted in a foregoing preparatory step.  
10       For example, when the solid support is an anionic exchange resin the immobilisation can be performed in a single step by mixing the resin with the catalyst in aqueous medium, followed by washing with water - or alternatively in two steps by first converting the resin  
15       to its hydroxyl form with a hydroxide such as aqueous sodium hydroxide, and then adding the catalyst.

      The alkylene oxides used as starting material in the process of the invention have their conventional definition, i.e. they are compounds having a vicinal  
20       oxide (epoxy) group in their molecules.

      Particularly suitable are alkylene oxides of the general formula



      wherein R<sup>1</sup> to R<sup>4</sup> independently represent a hydrogen atom or an, optionally substituted, alkyl group having  
25       from 1 to 6 carbon atoms. Any alkyl group, represented by R<sup>1</sup>, R<sup>2</sup>, R<sup>3</sup> and/or R<sup>4</sup> preferably has from 1 to 3 carbon atoms. As substituents, inactive moieties, such as hydroxy groups may be present. Preferably, R<sup>1</sup>, R<sup>2</sup> and R<sup>3</sup> represent hydrogen atoms and R<sup>4</sup> represents a non-  
30       substituted C<sub>1</sub>-C<sub>3</sub>-alkyl group and, more preferably, R<sup>1</sup>, R<sup>2</sup>, R<sup>3</sup> and R<sup>4</sup> all represent hydrogen atoms.



Examples of suitable alkylene oxides therefore include ethylene oxide, propylene oxide, 1,2-epoxybutane, 2,3-epoxybutane and glycidol. Ethylene oxide and propylene oxide are of particular commercial importance.

5       As mentioned above, it is advantageous to perform the hydrolysis of the alkylene oxides, without using excessive amounts of water. In the process according to the present invention, amounts of water in the range of 1 to 15 moles per mole of alkylene oxide are quite  
10       suitable, amounts in the range of 1 to 6 on the same basis being preferred. In the process of the invention high selectivities with respect to the monoalkylene glycol are often already achieved, when only 4 or 5 moles of water per mole of alkylene oxide are supplied.

15       The process of the invention may be carried out in batch operation. However, in particular for large scale embodiments it is preferred to operate the process continuously.

      Such continuous process can be carried out in a fixed  
20       bed reactor, operated in up-flow or down-flow. Down-flow operation is preferred.

      The reactor may be maintained under isothermal, adiabatic or hybrid conditions. Isothermal reactors are generally shell- and tube reactors, mostly of the  
25       multitubular type, wherein the tubes contain the catalyst and a coolant passes outside the tubes. Adiabatic reactors are not cooled, and the product stream leaving them may be cooled in a separate heat exchanger.

      Under certain chosen circumstances the catalytic  
30       conversion of EO may be incomplete, in which situation rest EO can be thermally hydrolysed in the dead space of the reactor below the catalyst bed. Since this thermal hydrolysis is less specific towards MEG, it is recommended to minimise the liquid hold-up in the  
35       reactor. This can be achieved by filling the reactor

outlet part with internals or inert packing material to reduce its volume, and/or by adding an inert gas, such as nitrogen, to the reactor feed mixture and operating the reactor under so-called trickle flow conditions.

5 In order to obtain adequate time-yield values, it is recommended to perform the process under elevated temperature and pressure conditions.

Suitable reaction temperatures are generally in the range from 80 to 200 °C, whereby temperatures in the  
10 range from 90 to 150 °C are preferred. The reaction pressure is usually selected in the range of 200 to 3000, preferably 200 to 2000 kPa. For batch operations of the process, the selected reaction pressure is advantageously obtained by pressurising with an inert gas, such as  
15 nitrogen. If desired, mixtures of gases may be used, for example a mixture of carbon dioxide and nitrogen is in certain instances advantageous.

In order to accommodate any swelling of the catalyst during operation, the reactor volume can advantageously  
20 be greater than the volume occupied by of the catalyst therein, for example 10 to 70 vol% greater.

It will be understood that the process of the present invention is not limited to its operation in the presence of the defined catalyst alone. In certain situations,  
25 particularly when operating in continuous-flow manner, it has been found to be advantageous to subject at least part, such as about 30-60 wt%, of the alkylene oxide feed stream to partial thermal hydrolysis in the absence of catalyst, before completing the hydrolysis catalytically.  
30 It has been found that partial hydrolysis, even in the absence of a catalyst, is still sufficiently selective towards the monoalkylene glycol while on the other hand this measure is effective in saving the catalyst.

A problem which may occasionally arise in any process  
35 wherein ethylene oxide is being hydrolysed is the

presence of small amounts of amines and/or phosphines as impurities in the product stream. When a strongly basic anion exchange resin according to the present invention is used as the solid support for the catalytic anion, the basic groups thereof are quaternary phosphonium groups. It has been found that during operation, small amounts of phosphines may leach from the resin into the product stream. Besides, the product stream may contain small amounts of amines which originate from corrosion inhibitors added to the water used in the process. Although the amounts of such amine and/or phosphine contaminants reaching the end-product are generally very small, they may affect the quality of the end-product such that it may be desirable to keep them below the detection level. For example, trimethylamine (TMA) and/or dimethylamine (DMA) may reach the end-product in an amount of up to 10 ppm while the fishy odour of TMA may be detected in an amount as low as 1 ppb.

An effective measure in removing amines and/or phosphines which may be present in the product stream of generally any process wherein ethylene oxide is being hydrolysed, including the process of the present invention, has been found to be the use of a guard-bed, containing a strongly acidic ion exchange resin which effectively captures the amines or phosphines. Strongly acidic ion exchange resins are of the sulphonic type. Commercially available examples are those known by the trademarks AMBERLYST 15, AMBERJET 1500H, AMBERJET 1200H, DOWEX MSC-1, DOWEX 50W, DIANON SK1B, LEWATIT VP OC 1812, LEWATIT S 100 MB and LEWATIT S 100 G1. These strongly acidic ion exchange resins are available in  $H^+$  form and in salt form, such as the  $Na^+$  form. When only the  $H^+$  form of the strongly acidic resin is used in the guard bed, the product stream after passing it may become acidic. Using a mixture of the strongly acidic ion exchange resin

in its  $H^+$  form and salt form has the advantage of the pH of the product stream remaining close to neutral.

5 An added advantage of the strongly acidic guard bed is that any remaining alkylene oxide which may be still present in the product stream is hydrolysed to alkylene glycol, albeit with a lesser selectivity towards the monoalkylene glycol.

10 In order to accommodate for exhaustion of the strongly acidic ion exchange resin during operation, it is advantageous to operate the guard bed in two or more separate vessels.

15 Exhausted strongly acidic ion exchange resin can be regenerated by treatment with an acid which is stronger than the sulphonic acid groups in the resin matrix, such as HCl and  $H_2SO_4$ . Hot sulphuric acid of 0.1-2 normality has been proven to be effective.

The following Examples will illustrate the invention.

#### Examples

##### 1. Preparation of catalysts

###### 20 1.1 Homogeneous bicarbonate catalysts

A quaternary phosphonium salt and a similar quaternary ammonium salt (for comparison) in hydroxide form were used as precursors for the bicarbonate catalysts under investigation:

- 25 - tetra-n-butylphosphonium hydroxide:  $(n-C_4H_9)_4P^+OH^-$   
- tetra-n-butylammonium hydroxide:  $(n-C_4H_9)_4N^+OH^-$

These bases were converted into the bicarbonate salts prior to use by stirring overnight under 1000 kPa of carbon dioxide:



###### 1.2 Catalysts based on strongly basic IER

- A strongly basic ion exchange resin of the quaternary phosphonium type (tributylmethylphosphonium bromide on a polystyrene/1% divinylbenzene polymer support

ex-Fluka, chloride form, exchange capacity 0.9 meq/g) was treated as follows to prepare the bicarbonate catalyst:

- 5       - 25 g of dry resin was stirred for 20 hours with 250 ml of demineralised water and 18.9 g (10 molar excess) of sodium bicarbonate ( $\text{NaHCO}_3$ ). After filtration this procedure was repeated three times
- 10       - the exchanged resin was washed with 1200 ml of water for 2 hours until no more chloride could be detected (with the help of  $\text{AgNO}_3$ ) in the wash water.
- 15       o A strongly basic ion exchange resin of the quaternary phosphonium type (EGL-660, monodisperse cross-linked polystyrene/divinylbenzene resin ex-Rohm & Haas, chloride form, exchange capacity 1.7 meq/g) was treated as follows to prepare the formate catalyst:
  - 100 g of wet (50 wt%) resin was slurried in a water filled glass tube (60 x 2.5 cm).
  - chloride was exchanged by treatment with 122.4 g sodium formate in aqueous solution (10 molar excess, 20       in 2500 g of water) for approximately 5 hours (LHSV: 4 l/h).
  - the exchanged resin was washed with 1200 ml of water for 2 hours (LHSV: 4 l/h) until no more chloride could be detected (with the help of  $\text{AgNO}_3$ ) in the wash 25       water.
- 30       o A strongly basic ion exchange resin of the quaternary ammonium type (AMBERJET 4200 (trademark), mono-disperse cross-linked polystyrene/divinylbenzene resin ex-Rohm & Haas, chloride form, exchange capacity 1.4 meq/ml) was treated as follows to prepare the bicarbonate or formate catalyst for comparison:
  - 150 ml of wet resin was slurried in a water filled glass tube (60 x 2.5 cm)
  - chloride was exchanged by treatment with 176.4 g 35       of sodium bicarbonate or 151.2 g of sodium formate in

aqueous solution (10 molar excess, in 2500 g of water) for approximately 5 hours (LHSV: 4 l/h)

5       - the exchanged resin was washed with 1200 ml of water for 2 hours (LHSV: 4 l/h) until no more chloride could be detected (with the help of  $\text{AgNO}_3$ ) in the wash water.

2. Batch EO hydrolysis reaction at 100 °C

10       A 250 ml autoclave was filled with the respective catalyst (30 mmol) and water (100 g; 5.55 mol). The gascap was purged 3 times with nitrogen and an initial pressure of 1000 kPa of  $\text{N}_2$  was employed. In Exp. 2.3 and 2.4 the mixture was stirred overnight at room temperature under  $\text{CO}_2$ . In all cases the mixture was heated to 100 °C. EO (44 g; 1 mol) was slowly added under stirring (500 rpm).  
15       The reaction mixture was maintained under continuous stirring for 6 hours at the reaction temperature. After cooling to room temperature (20 °C) stirring was continued overnight and an end of run sample was taken for GLC analysis.

20       The results of the catalytic EO batch hydrolysis experiments in terms of EO conversion and selectivity to MEG, using the phosphonium type of catalysts in bicarbonate form, and the results of reference experiments (no catalyst,  $\text{NaHCO}_3$ , AMBERJET 4200/bicarbonate and two  
25       tetraalkylammonium bicarbonate catalysts) are summarised in Table 1.

Table 1. Batch EO hydrolysis at 100 °C using phosphonium catalysts and comparison with similar ammonium catalysts

Exp. No.	Catalyst	Amount of catalyst (mmol)	EO conversion (mol%)*	Selectivity towards MEG (mol%)**
2.1 (ref.)	-	-	99.2	67.8
2.2 (ref.)	NaHCO <sub>3</sub>	30	99.7	85.0
2.3 (ref.)	tetra-n-butyl ammonium bicarbonate: (n-C <sub>4</sub> H <sub>9</sub> ) <sub>4</sub> N <sup>+</sup> HCO <sub>3</sub> <sup>-</sup>	30.1	>96	86.9
2.4	tetra-n-butyl phosphonium bicarbonate: (n-C <sub>4</sub> H <sub>9</sub> ) <sub>4</sub> P <sup>+</sup> HCO <sub>3</sub> <sup>-</sup>	30	>90	83.8
2.5	tributylmethyl phosphonium bicarbonate on PS/DVB (IER)	19	99.9	87.1
2.6 (ref.)	AMBERJET 4200/HCO <sub>3</sub> <sup>-</sup> (bicarbonate)	30	99.0	88.3
2.7	EGL-660/HCO <sub>2</sub> <sup>-</sup> (formate)	15	99.7	75.6
2.8 (ref.)	AMBERJET 4200/HCO <sub>2</sub> <sup>-</sup> (formate)	30	99.1	78.5

\* EO conversion (mol%) = 100 x (MEG+2DEG+3TEG)/-  
(EO+MEG+2DEG+3TEG)

\*\* Selectivity towards MEG (mol%) = 100 x MEG/-  
(MEG+2DEG+3TEG)

The results indicate that the phosphonium/bicarbonate catalysts (both homogeneous and on the polystyrene/divinylbenzene matrix) have a very attractive catalytic performance in terms of selectivity to MEG (83.8 and 87.1%, respectively). The performance is very similar to that of other bicarbonate type of catalysts.

### 3. Catalyst stability test

In order to compare the thermal stability of a quaternary phosphonium compounds with a similar quaternary ammonium compound, both were studied in hydroxide form, because such hydroxides are more sensitive to thermal degradation than the respective bicarbonate forms.

The thermal stability of tetrabutyl phosphonium hydroxide (TBPH) was evaluated and compared with the thermal stability of tetrabutyl ammonium hydroxide (TBAH). The hydroxides (a 40% aqueous solution of each) were kept at 100 °C in an autoclave for several days. At time intervals samples were taken for analysis. The decomposition of the quaternary bases was determined by Nuclear Magnetic Resonance (NMR) spectroscopy, using Carbon-13 ( $^{13}\text{C}$ ) NMR for the ammonium compounds and Phosphorus-31 ( $^{31}\text{P}$ ) NMR for the phosphonium compounds.

The NMR analysis showed that the thermal degradation product of the quaternary ammonium hydroxide TBAH was tri-n-butylamine (TBA), and that the thermal degradation product of the quaternary phosphonium hydroxide TBPH was tri-n-butylphosphine oxide (TBPO).

The results of these stability studies are summarised in Table 2.



Table 2.. Thermal stability test of a quaternary phosphonium catalyst in comparison with a similar quaternary ammonium catalyst


time (h)	TBPH (%mol)	TBPO (%mol)	TBAH (%mol)	TBA (%mol)
0	100	0	100	0
3-4	95	1	94	0
20-21	93	3	94	0.3
44-46	90	6	96	0.8
116-120	78	18	41	58

These results indicate that the thermal stability of a quaternary phosphonium compound is significantly better than the thermal stability of a similar quaternary ammonium compound.

C L A I M S

1. A process for the preparation of alkylene glycols by reacting an alkylene oxide with water in the presence of at least one ionic composition of a quaternary phosphonium cation of the general formula

5



Whereby each of  $R_1$ ,  $R_2$ ,  $R_3$  and  $R_4$ , independently, may be an alkyl, cycloalkyl, aryl, alkylaryl or arylalkyl group having from 1 to 10 carbon atoms, each of which may carry one or more substituents, or be attached to a polymer, and an anion other than metalate or halogen.

10

2. A process according to claim 1, whereby the anion is chosen from the group of bicarbonate, bisulphite and the carboxylic acid derivatives.

15

3. A process according to claim 2, whereby the anion is chosen from the group of formate and citrate.

4. A process according to any one of claims 1 to 3, whereby the quaternary phosphonium cation is immobilised on a solid support.

20

5. A process according to claim 4, whereby the solid support is an anion exchange resin.

# INTERNATIONAL SEARCH REPORT

International Application No

PCT/EP 99/10047

**A. CLASSIFICATION OF SUBJECT MATTER**  
IPC 7 C07C29/10

According to International Patent Classification (IPC) or to both national classification and IPC

**B. FIELDS SEARCHED**

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 C07C

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

**C. DOCUMENTS CONSIDERED TO BE RELEVANT**

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	GB 2 086 894 A (ICI) 19 May 1982 (1982-05-19) claim 3; example 4	1,2
A	US 4 160 116 A (M. MIENO, ET AL.) 3 July 1979 (1979-07-03) cited in the application the whole document	1
A	WO 95 20559 A (SHELL INTERNATIONALE RESEARCH) 3 August 1995 (1995-08-03) cited in the application page 3, line 27 -page 4, line 5; claim 1	1
A	EP 0 160 330 A (UNION CARBIDE) 6 November 1985 (1985-11-06) cited in the application page 9 -page 11	1

☐ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

\* Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

24 February 2000

Date of mailing of the international search report

03/03/2000

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,  
Fax: (+31-70) 340-3016

Authorized officer

English, R

# INTERNATIONAL SEARCH REPORT

information on patent family members

International Application No

PCT/EP 99/10047

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
GB 2086894 A	19-05-1982	NONE	
US 4160116 A	03-07-1979	CA 1126725 A	29-06-1982
WO 9520559 A	03-08-1995	AU 681937 B	11-09-1997
		AU 1537495 A	15-08-1995
		CN 1139916 A	08-01-1997
		CZ 9602043 A	13-11-1996
		DE 69505641 D	03-12-1998
		DE 69505641 T	08-04-1999
		EP 0741683 A	13-11-1996
		ES 2122540 T	16-12-1998
		JP 9508136 T	19-08-1997
		NZ 278896 A	20-12-1996
		SG 47916 A	17-04-1998
		SK 92796 A	05-03-1997
		US 5488184 A	30-01-1996
EP 0160330 A	06-11-1985	AT 58718 T	15-12-1990
		AU 579624 B	01-12-1988
		AU 4153585 A	01-11-1985
		BR 8506207 A	15-04-1986
		CA 1314566 A	16-03-1993
		DD 238786 A	03-09-1986
		ES 541613 A	16-04-1986
		JP 5047528 B	19-07-1993
		JP 61501630 T	07-08-1986
		KR 9107570 B	28-09-1991
		PL 252629 A	03-12-1985
		WO 8504393 A	10-10-1985
		US 4982021 A	01-01-1991